







### LS563LED-2-D-1W2-21

Vedi with 316 stainless steel cover, 1W white LED source, 12V AC / 24V DC



Direct Burial



Pre-Installation /  
Concrete Blockout

## SPECIFICATIONS

<b>Lamp Source</b>	1W Luxeon K2 LED
<b>Voltage</b>	Line voltage: 110-240V AC, 50/60 Hz Low voltage: 12V AC (Magnetic trans. only) 24V DC (Ripple free supply) <small>NOTE: Low voltage requires remote driver / transformer. Optional remote constant current driver. Refer to C1916 for Transformers &amp; Drivers. Order separately.</small>
<b>LED Colours</b>	<input type="checkbox"/> White (5300K typ.) <input type="checkbox"/> Warm white (3300K typ.) <input checked="" type="checkbox"/> Blue <small>Availability of other colours on request. Minimum order quantities may apply.</small>
<b>IP Rating</b>	IP68
<b>Housing Material / Finish</b>	316 stainless steel
<b>Cover Material / Finish</b>	316 stainless steel Brass Powdercoat (Brass only) <input checked="" type="checkbox"/> Black <input type="checkbox"/> White <input type="checkbox"/> Silver <small>Custom powdercoat colours available</small>
<b>Lens / Options</b>	Toughened glass
<b>Mounting Options</b>	Direct burial <b>LS698-K</b> Pre-installation concrete blockout. <small>Order separately.</small>
<b>Drive-over Option</b>	<b>LS698-K</b> Pre-installation concrete blockout. <small>Order LS698-K separately.</small>
<b>Cable length</b>	3m standard <small>Other lengths available on request.</small>
<b>Static Load Rating</b>	1100kg
<b>Impact Rating</b>	IK7
<b>Ambient Temp. Rating</b>	-20°C to 50°C
<b>Warranty</b>	10 year structural 12 month electrical

### HOW TO SPECIFY...

PRODUCT	COVER	SOURCE	INSTALLATION TYPE						
CODE	FINISH	CODE	VOLTAGE	CODE	WATTAGE	COLOUR	CODE	DESCRIPTION	CODE
LS563LED	Stainless Steel	2	110V - 240V AC	I	1W	White	1W2	Standard	21
	Brass	3	12V AC / 24V DC	D		Warm White	1H2	Pre-install	23
	Powdercoated: Black	4				Blue	1B2		
	Powdercoated: White	5							
	Powdercoated: Silver	6							

**EXAMPLE** **LS563LED-2-I-1H2-23 with LS698-K** Vedi with 316 stainless steel cover, 1W warm white LED source, for pre-installation, 12V AC / 24V DC, with LS698-K pre-installation concrete blockout for drive-over