





The LS454 is a luminaire designed for use in external ceiling areas where a recessed downlight is not practical. As an IP67 rated luminaire, the protection against water ingress is excellent, making it suitable for use in exterior applications. In both LED and Halogen variants, the light output is diffused.

SPECIFICATIONS

LED Source	LED 3 W ⁽¹⁾ <input type="checkbox"/> White (4300 K typical) <input type="checkbox"/> Warm white (3000 K typical) <input type="checkbox"/> Blue (470 nm) <i>Other colours by request</i>
IP Rating	IP67
Construction	Powder coated aluminium <input type="checkbox"/> Black <input type="checkbox"/> Silver <input type="checkbox"/> Superchrome
Installation Type	Surface ceiling mount
Standard Inclusions	Integral driver with field intensity setting (page 242) Toughened diffuser lens
Ambient Operating Temperature	-20 °C to +50 °C
Warranty	2 year structural, 1 year electrical
Photometrics	Go to www.lumascape.com.au ▶ Technical Data ▶ Photometric Files



LS454LED Aura



NOTE: Product specifications are subject to change without notice. Any luminaire can become hot - take care with appropriate use and placement.

⁽¹⁾ Nominal power consumption only, actual power consumed may vary.

CONFIGURE THIS PRODUCT >

LS454LED			7				
LED SOURCE			SUPPLY VOLTAGE		FINISH		
Wattage	Colour	Code	Voltage	Code	Description	Material	Code
3 W	White (4300 K typical)	3W4	24 V DC or 12 V AC ⁽¹⁾	7	Powder coated black	Aluminium	CB
	Warm white (3000 K typical)	3H6			Powder coated anodic silver	Aluminium	CS
	Blue (470 nm)	3B4			Powder coated Superchrome	Aluminium	CA

⁽¹⁾ Requires remote power supply or transformer - see page 239.